

Вентиляторы Profantec

Минск www.fotorele.net www.tiristor.by радиодетали, электронные компоненты

email minsk17@tut.by tel.mob +375 44 758 47 80 velcom +375 29 758 47 80 МТС

каталог, описание, технические, характеристики, datasheet, параметры, маркировка, габариты, фото, даташит, profantec

QR код

The image shows a product page for Profan fans. At the top, it says 'Вентилятор PROFAN 220VAC 115VAC 230VAC 110VAC VDC'. Below this is a blue banner with 'HIGH AIRFLOW / SAVE POWER' and an image of several fans. To the left is a navigation menu with 'Product' and 'AC Speed Fans'. In the center, there is a circular logo for 'Беларусь Минск' with contact information: www.fotorele.net, www.tiristor.by, email minsk17@tut.by, and tel. +375447584780. To the right is a QR code labeled 'QR код'.

- 15x15x04, 15x15x06, 20x20x06, 20x20x10, 25x25x06, 25x25x10, 25x25x15, 30x30x06, 30x30x10, 30x30x15, 35x35x06, 35x35x10, 38x38x28, 40x40x06, 40x40x10, 40x40x15, 40x40x20, 40x40x28, 40x40x56, 45x45x06, 45x45x10, 50x50x10, 50x50x15, 50x50x20, 60x60x10, 60x60x15, 60x60x20, 60x60x25, 60x60x38, 60x60x76, 70x70x15, 70x70x20, 70x70x25, 80x80x15, 80x80x20, 80x80x25, 80x80x32, 80x80x38, 80x80x76, 92x92x20, 92x92x32, 92x92x25, 92x92x38, 105x105x38, 113x113x36, 120x120x25, 120x120x32, 120x120x38, 127x127x38, 135x135x25, 140x140x38, 140x140x51, 172x150x51, AC-fan, Радиальные-Blowers, Влагостойкие, 80x80x25, AC, 80x80x38 AC 92x92x25 AC 120x120x25 AC 120x120x38 AC 172x150x38 AC 172x150x51 AC 172x150x55 AC 254x254x89 AC
- 25x25x10 DC 30x30x6 DC 30x30x10 DC 40x40x7 DC 40x40x10 DC 50x50x15 DC
- 60x60x15 DC
- 60x60x20 DC
- 60x60x25 DC
- 70x70x25 DC
- 80x80x15 DC
- 80x80x25 DC
- 80x80x25 AC
- 80x80x38 AC
- 92x92x25 AC
- 120x120x25 AC
- 120x120x38 AC
- 172x150x38 AC
- 172x150x51 AC
- 172x150x55 AC
- 254x254x89 AC
- 25x25x10 DC
- 30x30x6 DC
- 30x30x10 DC
- 40x40x7 DC
- 40x40x10 DC
- 50x50x15 DC
- 60x60x15 DC
- 60x60x20 DC
- 60x60x25 DC
- 70x70x25 DC
- 80x80x15 DC
- 80x80x25 DC

вентилятор с металлическими лопастями и корпусом

вентилятор profan

даташит datasheet вентилятор proFAN

Вентилятор переменного тока

- Product Name : **120x120x31**



Product



[80x80x25mm](#)

[вентилятор переменного тока](#)



[120X120X38](#)

[вентилятор переменного тока](#)



[120X120X38\(7 blades\)](#)

[вентилятор переменного тока](#)



[127x127x38mm](#)

[вентилятор переменного тока](#)



[172x150x51mm](#)

[вентилятор переменного тока](#)



[172x150x38mm](#)

[вентилятор переменного тока](#)



[176X176X89mm](#)

[вентилятор переменного тока](#)



[205X205X72mm](#)

[вентилятор переменного тока](#)





[254X254X89mm](#)

[вентилятор переменного тока](#)



[172x150x51](#)

[вентилятор переменного тока](#)



Features :

Specification :

Модель	Safety Std.	Voltage (V)	Freq. (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
PB1123HS T	UL	115	50/60	0.24/0.22	21/19	2650/3000	18/20	0.34/0.5	45/48
PB1123HS L	UL	115	50/60	0.24/0.22	21/19	2650/3000	18/20	0.34/0.5	48/48
PB1123HB T	UL	115	50/60	0.24/0.22	21/19	2650/3000	18/20	0.34/0.5	45/48
PB1123HB L	UL	115	50/60	0.24/0.22	21/19	2650/3000	18/20	0.34/0.5	45/48

PB2123HS T	TUV,C E	230	50/6 0	0.13/0.1 1	21/19	2650/300 0	18/20	0.34/0.5	45/4 8
PB2123HS L	TUV,C E	230	50/6 0	0.13/0.1 1	21/19	2650/300 0	18/20	0.34/0.5	45/4 8
PB2123HB T	TUV,C E	230	50/6 0	0.13/0.1 1	21/19	2650/300 0	18/20	0.34/0.5	45/4 8
PB2123HB L	TUV,C E	230	50/6 0	0.13/0.1 1	21/19	2650/300 0	18/20	0.34/0.5	45/4 8

AC Plastic Вентиляторы

- Item No. : **172x150x51**
- Product Name : **вентилятор переменного тока**



описание, технические характеристики

1. Frame: Die cast aluminum
2. Impeller: Thermoplastic PBT V-0
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range: Rated Voltage ±10%
5. Bearing: Ball
6. Motor Structure: AC induction capacitor Motor
7. Motor Protection: Thermal or Impedance Protected
8. Termination: Terminals or Lead wire 280±15mm
9. Packing: 908g/pcs , 12pcs/CTN

Features :

1. Inside rotor motor design

Specification :

Модель	Safety Std.	Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P1175HB T	UL	115	50/60	0.22/0.23	25/27	2800/3300	202/240	0.6/0.73	51/58
P1175HB L	UL	115	50/60	0.22/0.23	25/27	2800/3300	202/240	0.6/0.73	51/58
P2175HB T	UL,TUV	230	50/60	0.12/0.12	25/27	2800/3300	202/240	0.6/0.73	51/58
P2175HB L	UL,TUV	230	50/60	0.12/0.12	25/27	2800/3300	202/240	0.6/0.73	51/58

AC Plastic Вентиляторы

- Item No. : **254X254X89mm**
- Product Name : **вентилятор переменного тока**



1. Frame: Die cast aluminum
2. Impeller: Thermoplastic PBT V-0
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range: Rated Voltage±10%
5. Bearing: Ball
6. Motor Structure: AC induction capacitor Motor
7. Motor Protection: Thermal Protected
8. Termination: Terminals or Lead wire 310±15mm
9. Packing: 2000g/pcs , 6pcs/CTN

Features :

1. The Вентилятор have middle and high speed type

Specification :

Модель	Safety Std.	Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P1259MBT	UL	115	50/60	0.22/0.23	23/26	1400/1600	600/665	0.22/0.25	50/52
P1259MBL	UL	115	50/60	0.22/0.23	23/26	1400/1600	600/665	0.22/0.25	50/52
P2259MBT	UL	230	50/60	0.15/0.13	30/30	1400/1600	400/665	0.22/0.25	50/52
P2259MBL	UL	230	50/60	0.15/0.13	30/30	1400/1600	600/665	0.22/0.25	50/52
P1259HBT	UL	115	50/60	0.6/0.65	63/72	2100/1900	730/710	0.35/0.28	57/55
P1259HBL	UL	115	50/60	0.6/0.65	63/72	2100/1900	730/710	0.35/0.28	57/55
P2259HBT	UL	230	50/60	0.24/0.27	56/60	2100/1900	730/710	0.35/0.28	57/55
P2259HBL	UL	230	50/60	0.24/0.27	56/60	2100/1900	730/710	0.35/0.28	57/55

- Item No. : **205X205X72mm**
- Product Name : **вентилятор переменного тока**



описание, технические характеристики

1. Frame: Die cast aluminum
2. Impeller: Thermoplastic PBT V-0
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range: Rated Voltage ±10%
5. Bearing: Ball
6. Motor Structure: AC induction capacitor Motor
7. Motor Protection: Thermal Protected
8. Termination: Terminals or Lead wire 350±15mm
9. Packing: 2100g/pcs , 6pcs/CTN

Features :

1. AC induction capacitor motor design
2. It is the highest airflow in our owned Вентилятор series

Specification :

Модель	Safety Std.	Voltage (V)	Freq. (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P1207HBL	UL	115	50/60	0.61/0.86	65/102	2850/3200	630/660	0.97/1.09	61/64

P2207HBL	UL	230	50/60	0.32/0.45	63/95	2850/3200	630/660	0.97/1.09	61/64
----------	----	-----	-------	-----------	-------	-----------	---------	-----------	-------

- Item No. : **176X176X89mm**
- Product Name : **вентилятор переменного тока**



описание, технические характеристики

1. Frame:Die cast aluminum
2. Impeller:Thermoplastic PBT V-0
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range:Rated Voltage \pm 10%
5. Bearing: Ball
6. Motor Structure:AC induction capacitor Motor
7. Motor Protection:Thermal Protected
8. Termination:Terminals or Lead wire 310 \pm 15mm
9. Packing:1960g/pcs , 6pcs/CTN

Features :

- 1.AC induction capacitor motor design
- 2.Low current
- 3.The hub of blade is closed to avert dust

Specification :

Модель	Safety Std.	Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H2O)	Noise (dB)
P1189HBT	UL	115	50/60	0.26/0.26	25/30	2850/3350	300/350	0.69/0.8	58/62
P1189HBL	UL	115	50/60	0.26/0.26	25/30	2850/3350	300/350	0.69/0.8	58/62
P2189HBT	UL,TUV	230	50/60	0.12/0.16	25/30	2850/3350	300/350	0.69/0.8	58/62
P2189HBL	UL,TUV	230	50/60	0.12/0.16	25/30	2850/3350	300/350	0.69/0.8	58/62

- Item No. : **172x150x38mm**
- Product Name : **вентилятор переменного тока**



описание, технические характеристики

1. Frame: Die cast aluminum
2. Impeller: Thermoplastic PBT V-0
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range: Rated Voltage ±10%
5. Bearing: Ball
6. Motor Structure: AC External rotor capacitor Motor
7. Motor Protection: Thermal or Impedance Protected

8. Termination: Terminals or Lead wire 280±15mm
 9. Packing: 730g/pcs , 12pcs/CTN

Features :

1. External rotor motor
2. Low power consumption
3. Motor can design three-phase and 4-pole type

Specification :

Модель	Safety Std.	Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P1173HBT-ET	UL	115	50/60	0.23/0.23	25/26	2650/3200	200/225	0.58/0.62	55/58
P1173HBL-ET	UL	115	50/60	0.23/0.23	25/26	2650/3200	200/225	0.58/0.62	55/58
P2173HBT-ET	UL, TUV	230	50/60	0.12/0.12	25/26	2650/3200	200/225	0.58/0.62	55/58
P2173HBL-ET	UL, TUV	230	50/60	0.12/0.12	25/26	2650/3200	200/225	0.58/0.62	55/58

- Item No. : **172x150x51mm**
- Product Name : **вентилятор переменного тока**



описание, технические характеристики

1. Frame: Die cast aluminum
2. Impeller: Thermoplastic PBT V-0
3. Ambient Temperature Range: $-10^{\circ}\text{C} \sim +70^{\circ}\text{C}$
4. Operating Voltage Range: Rated Voltage $\pm 10\%$
5. Bearing: Ball
6. Motor Structure: AC External rotor capacitor Motor
7. Motor Protection: Thermal Protected
8. Termination: Terminals or Lead wire $280 \pm 15\text{mm}$
9. Packing: 790g/pcs , 12pcs/CTN

Features :

1. External rotor motor
2. Low power consumption
3. Motor can design three-phase and 4-pole type

Specification :

Модель	Safety Std.	Voltage (V)	Freq. (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P1175HB T-ET	UL	115	50/60	0.23/0.22	25/24	2700/3200	202/240	0.6/0.68	51/58

P1175HB L-ET	UL	115	50/60	0.23/0.2 2	25/24	2700/32 00	202/24 0	0.6/0.68	51/5 8
P2175HB T-ET	UL,TU V	230	50/60	0.12/0.1 2	25/25	2700/32 00	202/24 0	0.6/0.68	51/5 8
P2175HB L-ET	UL,TU V	230	50/60	0.12/0.1 2	25/25	2700/32 00	202/24 0	0.6/0.68	51/5 8
P3175HB T-ET	380	50/60	0.07/0.0 7	27/27	2700/32 00	202/240	0.6/0.6 8	51/58	
P3175HB L-ET	380	50/60	0.07/0.0 7	27/27	2700/32 00	202/240	0.6/0.6 8	51/58	

- Item No. : **127x127x38mm**
- Product Name : **вентилятор переменного тока**



описание, технические характеристики

1. Frame:Die cast aluminum
2. Impeller:Thermoplastic PBT V-0
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range:Rated Voltage±10%
5. Bearing: Sleeve or Ball
6. Motor Structure:AC shaded-pole Motor
7. Motor Protection:Impedance Protected
8. Termination:Terminals or Lead wire 310±15mm
9. Packing:566g/pcs , 40pcs/CTN

Features :

Specification :

Модель	Safety Std.	Voltage (V)	Freq. (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P1133HSL	UL	115	50/60	0.3/0.23	21/19	2650/3050	110/125	0.3/0.33	50/52
P1133HST		115	50/60	0.3/0.23	21/19	2650/3050	110/125	0.3/0.33	50/52
P1133HBT		115	50/60	0.3/0.23	21/19	2650/3050	110/125	0.3/0.33	50/52
P1133HBL		115	50/60	0.3/0.23	21/19	2650/3050	110/125	0.3/0.33	50/52
P2133HSL	UL,TUV	230	50/60	0.14/0.12	21/19	2600/3050	110/125	0.3/0.33	50/52
P2133HST		230	50/60	0.14/0.12	21/19	2600/3050	110/125	0.3/0.33	50/52
P2133HBT	UL	230	50/60	0.14/0.12	21/19	2600/3050	110/125	0.3/0.33	50/52
P2133HBL	UL	230	50/60	0.14/0.12	21/19	2600/3050	110/125	0.3/0.33	50/52

- Item No. : **120X120X38(7 blades)**
- Product Name : **вентилятор переменного тока**



описание, технические характеристики

1. Frame: Die cast aluminum
2. Impeller: Thermoplastic PBT V-0
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range: Rated Voltage ±10%
5. Bearing: Sleeve or Ball
6. Motor Structure: AC shaded-pole Motor
7. Motor Protection: Impedance Protected
8. Termination: Terminals or Lead wire 310±15mm
9. Packing: 539g/pcs , 40pcs/CTN

Features :

1. Flowing shape
2. Seven blades
3. High Airflow

Specification :

Модель	Safety Std.	Voltage (V)	Freq. (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P1123HS T	UL	115	50/60	0.28/0.25	23/21	2500/2800	108/120	0.3/0.33	45/48

P1123HS L	UL	115	50/6 0	0.28/0.2 5	23/21	2500/275 0	108/12 0	0.3/0.33	45/4 8
P1123HB T	UL	115	50/6 0	0.28/0.2 5	23/21	2500/275 0	108/12 0	0.3/0.33	45/4 8
P1123HB L	UL	115	50/6 0	0.28/0.2 5	23/21	2500/275 0	108/12 0	0.3/0.33	45/4 8
P2123HS T	UL,TU V	230	50/6 0	0.14/0.1 2	24/22	2560/280 0	108/12 0	0.3/0.33	45/4 8
P2123HS L	UL,TU V	230	50/6 0	0.14/0.1 2	24/22	2560/280 0	108/12 0	0.3/0.33	45/4 8
P2123HB T	UL,TU V	230	50/6 0	0.14/0.1 2	24/22	2560/280 0	108/12 0	0.3/0.33	45/4 8
P2123HB L	UL,TU V	230	50/6 0	0.14/0.1 2	24/22	2560/280 0	108/12 0	0.3/0.33	45/4 8

- Item No. : **120X120X38**
- Product Name : **вентилятор переменного тока**



описание, технические характеристики

1. Frame: Die cast aluminum
2. Impeller: Thermoplastic PBT V-0
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range: Rated Voltage ±10%
5. Bearing: Sleeve or Ball

- 6. Motor Structure: AC shaded-pole Motor
- 7. Motor Protection: Impedance Protected
- 8. Termination: Terminals or Lead wire 310±15mm
- 9. Packing: 506g/pcs , 40pcs/CTN

Features :

1. Flowing shape

Specification :

Модель	Safety Std.	Voltage (V)	Freq. (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P1123HS T	UL	115	50/60	0.21/0.18	17/15.5	2700/3150	97/115	0.27/0.34	47/49
P1123HS L	UL	115	50/60	0.21/0.18	17/15.5	2700/3150	97/115	0.27/0.34	47/49
P1123HB T	UL	115	50/60	0.21/0.18	17/15.5	2700/3150	97/115	0.27/0.34	47/49
P1123HB L	UL	115	50/60	0.21/0.18	17/15.5	2700/3150	97/115	0.27/0.34	47/49
P2123HS T	UL, TUV, CE	230	50/60	0.12/0.1	20/17	2700/3150	97/115	0.27/0.34	47/49
P2123HS L	UL, TUV, CE	230	50/60	0.12/0.1	20/17	2700/3150	97/115	0.27/0.34	47/49
P2123HB T	UL, TUV, CE	230	50/60	0.12/0.1	20/17	2700/3150	97/115	0.27/0.34	47/49
P2123HB L	UL, TUV, CE	230	50/60	0.12/0.1	20/17	2700/3150	97/115	0.27/0.34	47/49

- Item No. : **80x80x25mm**
- Product Name : **вентилятор переменного тока**



описание, технические характеристики

1. Frame:Die cast aluminum
2. Impeller:Thermoplastic PBT V-0
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range:Rated Voltage \pm 10%
5. Bearing: Sleeve
6. Motor Structure:DC Motor
7. Motor Protection:Impedance Protected
8. Termination:Terminals or Lead wire 230 \pm 15mm
9. Packing:135g/pcs , 40pcs/CTN

Features :

- 1.The hub of blade is small
- 2.Seven blades, high airflow
- 3.Over 3600rpm limit
- 4.Ensure surge voltage \pm 30%

Specification :

Модель	Safety Std.	Voltage (V)	Freq. (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P1082HS T	UL	115	50/60	0.14/0.16	3.5/4.5	3300/3700	42/48	0.18/0.22	33/35
P1082HS L	UL	115	50/60	0.14/0.16	3.5/4.5	3300/3700	42/48	0.18/0.22	33/35
P2082HS T	TUV,CE	230	50/60	0.14/0.17	4/5.5	3700/4100	42/48	0.18/0.22	35/37
P2082HS L	TUV,CE	230	50/60	0.14/0.17	4/5.5	3700/4100	42/48	0.18/0.22	35/37



[172X150X55](#)
[AC Steel Ventilator](#)



[172x150x55 8 blade](#)
[AC steel Ventilator](#)





[172x150x51](#)
[AC Steel Вентилятор](#)



[172x150x51 8 blade](#)
[AC steel Вентилятор](#)



[120x120x38](#)
[AC Steel Вентилятор](#)



[172x150x38](#)
[AC Steel Вентилятор](#)

- Item No. : **172x150x38**
- Product Name : **AC Steel Вентилятор**



описание, технические характеристики

1. Frame:Die cast aluminum
2. Impeller:Steel
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range:Rated Voltage±10%
5. Bearing: Ball
6. Motor Structure:AC External rotor capacitor Motor
7. Motor Protection:Thermal or Impedance Protected
8. Termination:Terminals or Lead wire 280±15mm
9. Packing:800g/pcs , 12pcs/CTN

Features :

- 1.External rotor motor
- 2.High airflow
- 3.Motor can design three-phase and 4-pole type

Specification :

Модель	Safety Std.	Voltage (V)	Freq. (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P1173HBT	UL	115	50/6	0.2/0.2	24/24	2700/320	205/23	0.48/0.5	56/5

-ETS			0			0	0	6	9
P1173HBL -ETS	UL	115	50/6 0	0.2/0.2	24/24	2700/320 0	205/23 0	0.48/0.5 6	56/5 9
P2173HBT -ETS	UL,TU V	230	50/6 0	0.1/0.1	24/24	2700/320 0	205/23 0	0.48/0.5 6	56/5 9
P2173HBL -ETS	UL,TU V	230	50/6 0	0.1/0.1	24/24	2700/320 0	205/23 0	0.48/0.5 6	

- Item No. : **120x120x38**
- Product Name : **AC Steel Вентилятор**



описание, технические характеристики

1. Frame:Die cast aluminum
2. Impeller:Steel
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range:Rated Voltage±10%
5. Bearing: Ball
6. Motor Structure:AC External rotor capacitor Motor
7. Motor Protection:Impedance Protected
8. Termination:Terminals or Lead wire 310±15mm
9. Packing:534g/pcs , 40pcs/CTN

Features :

- 1.It is suitable for particular environment, ex: UV light, high temperature...etc.
- 2.Low current
- 3.High airflow

Specification :

Модель	Safety Std.	Voltage (V)	Freq. (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H2O)	Noise (dB)
P1123HS T-ES	UL,	115	50/60	0.13/0.11	12.5/11	2750/3250	105/123	0.28/0.35	47/49
P1123HS L-ES	UL,	115	50/60	0.13/0.11	12.5/11	2750/3250	105/123	0.28/0.35	47/49
P1123HB T-ES	UL,	115	50/60	0.13/0.11	12.5/11	2750/3250	105/123	0.28/0.35	47/49
P1123HB L-ES	UL,	115	50/60	0.13/0.11	12.5/11	2750/3250	105/123	0.28/0.35	47/49
P2123HS T-ES	UL,TUV,CE	230	50/60	0.06/0.06	12.5/11.5	2650/3150	103/120	0.28/0.35	47/49
P2123HS L-ES	UL,TUV,CE	230	50/60	0.06/0.06	12.5/11.5	2650/3150	103/120	0.28/0.35	47/49
P2123HB T-ES	UL,TUV,CE	230	50/60	0.06/0.06	12.5/11.5	2650/3150	103/120	0.28/0.35	47/49
P2123HB L-ES	UL,TUV,CE	230	50/60	0.06/0.06	12.5/11.5	2650/3150	103/120	0.28/0.35	47/49

- Item No. : **172x150x51 8 blade**
- Product Name : **AC steel Вентилятор**



описание, технические характеристики

1. Frame:Die cast aluminum
2. Impeller:Steel
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range:Rated Voltage±10%
5. Bearing: Ball

- 6. Motor Structure: AC External Rotor Capacitor Motor
- 7. Motor Protection: Thermal or Impedance Protected
- 8. Termination: Terminals or Lead wire 300±15mm
- 9. Packing: 1000g/pcs , 12pcs/CTN

Features :

- 1. External rotor motor
- 2. 8 Steel blades
- 3. Low Current consumption
- 4. Motor can design three-phase and 4-pole type

Specification :

Модель	Safety Std.	Voltage (V)	Freq. (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P1175HBL-ETS	UL	115	50/60	0.28/0.26	30/28	2700/3100	235/265	0.59/0.7	52/55
P2175HBL-ETS	UL, TUV	230	50/60	0.14/0.13	30/28	2700/3100	235/265	0.59/0.7	52/55

- Item No. : **172x150x51**
- Product Name : **AC Steel Вентилятор**



описание, технические характеристики

1. Frame:Die cast aluminum
2. Impeller:Steel
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range:Rated Voltage±10%
5. Bearing: Ball
6. Motor Structure:AC External rotor capacitor Motor
7. Motor Protection:Thermal or Impedance Protected
8. Termination:Terminals or Lead wire 280±15mm
9. Packing:860g/pcs , 12pcs/CTN.

Features :

- 1.External rotor motor
- 2.low power consumption
- 3.Motor can design three-phase and 4-pole type

Specification :

Модель	Safety Std.	Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P1175HBT-ETS	UL	115	50/60	0.17/0.2	21/23	2750/3150	210/247	0.560.62	5457
P1175HBL-ETS	UL	115	50/60	0.17/0.2	21/23	2750/3150	210/247	0.560.62	5457
P2175HBT-ETS	UL,TUV	230	50/60	0.1/0.1	23/23	2750/3150	210/247	0.560.62	5457
P2175HBL-ETS	UL,TUV	230	50/60	0.1/0.1	23/23	2750/3150	210/247	0.560.62	5457

- Item No. : **172x150x55 8 blade**
- Product Name : **AC steel Вентилятор**



описание, технические характеристики

1. Frame: Die cast aluminum
2. Impeller: Steel
3. Ambient Temperature Range: $-10^{\circ}\text{C} \sim +70^{\circ}\text{C}$
4. Operating Voltage Range: Rated Voltage $\pm 10\%$
5. Bearing: Ball
6. Motor Structure: AC External Rotor Capacitor Motor
7. Motor Protection: Thermal or Impedance Protected
8. Termination: Terminals or Lead wire $300 \pm 15\text{mm}$
9. Packing: 1000g/pcs , 12pcs/CTN

Features :

1. External rotor motor
2. 8 Steel blades
3. Low Current consumption
4. Motor can design three-phase and 4-pole type

Specification :

Модель	Safety Std.	Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P11755HB L-ES		115	50/60	0.25/0.23	26/25	2750/3200	220/250	0.55/0.6	55/59
P21755HB L-ES	UL,TUV,CE	230	50/60	0.14/0.13	30/28	2700/3100	230/265	0.6/0.78	52/55

- Item No. : **172X150X55**

- Product Name : AC Steel Вентилятор



описание, технические характеристики

1. Frame:Die cast aluminum
2. Impeller:Steel
3. Ambient Temperature Range: -10°C ~ +70°C
4. Operating Voltage Range:Rated Voltage±10%
5. Bearing: Ball
6. Motor Structure:AC External Rotor Capacitor Motor
7. Motor Protection:Thermal or Impedance Protected
8. Termination:Terminals or Lead wire 300±15mm
9. Packing:850g/pcs , 12pcs/CTN

Features :

1. External rotor motor
2. Low Current consumption
3. Motor can design three-phase and 4-pole type

Specification :

Модель	Safety Std.	Voltage (V)	Freq. (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (in-H ₂ O)	Noise (dB)
P11755HB L-ES		115	50/60	0.25/0.23	26/25	2750/3200	220/250	0.55/0.6	55/59

P21755HB L-ES	UL,TUV,C E	230	50/6 0	0.14/0.1 3	30/28	2700/310 0	230/26 5	0.6/0.78	52/5 5
------------------	---------------	-----	-----------	---------------	-------	---------------	-------------	----------	-----------

DC steel Вентилятор

- Item No. : **172x150x55mm**
- Product Name : **DC48V 8blade**



Trade Information

- Country of Origin : Taiwan
- Main Export Markets :
- Payment Details :
- Payment Terms :
- Minimum Order :
- Delivery Details :
- Lead Time : Days
- FOB Port :

описание, технические характеристики

Frame: Die cast aluminum

Impeller: Steel

Ambient Temperature: -10°C ~ +70°C

Operating Voltage range: 32~56VDC 60VMax

Bearing: Ball

Motor Structure: Three phase Brushless motor

Motor protection: Thermal Protected

Termination: Lead wire 300±15mm

Package: 850g/PC, 12PCS/CTN

Features :

1. Three phase Brushless motor
2. Steel Вентилятор
3. FG and control line

Specification :

Rated Voltage: 48VDC

Line: 2 lines or 4 lines

Rated speed($\pm 10\%$): 3500rpm

Airflow: 295 cfm

Static pressure: 0.91in-H₂O

Rated current: 0.7A

Power: 33W

Noise: 58 db

Direction of Rotation: clockwise viewed front Вентилятор blade

- Item No. : **172X150X51mm**
- Product Name : **DC48V 5blade**



описание, технические характеристики

1. Rated Voltage : 48VDC
2. Operating Voltage Range : 32~56VDC 60VMax
3. Line : +: red -:black Signal: yellow Sp: blue
4. Rated Speed: ($\pm 10\%$) : 3400 rpm
5. Airflow : 295CFM
6. Static Pressure: 0.91in-H₂O
7. Rated Current : 0.6 A
8. Power: 29W
9. Noise : 58dB
10. Direction of Rotation : clockwise viewed front Вентилятор blade
11. Connect : Line 310+-15mm
12. Operating Temperature : -10 to +70Deg.C

13. Bearing System : Bearing System

14. Weight : 900g

15. IP Level : IP52 up

решётки вентиляторов



[12 CM](#)

[mental Вентилятор guard](#)




[17 CM](#)

[mental Вентилятор guard](#)



[20 CM](#)

[mental Вентилятор guard](#)



[3 in 1](#)

[three in one filter](#)



[8 CM](#)
[mental Вентилятор guard](#)



[SPT1](#)
[plug cords](#)



[SPT2](#)
[plug cords](#)

[даташит datasheet вентилятор proВентилятор](#)

Вентиляторы Profan

Минск www.fotorele.net www.tiristor.by радиодетали, электронные компоненты

email minsk17@tut.by tel.mob +375 44 758 47 80 velcom +375 29 758 47 80 МТС

каталог, описание, технические, характеристики, datasheet, параметры, маркировка, габариты, фото, даташит, profan